

digi-MOD Quad Input DVB-T Modulator

Part # RL-HD4001DM



FRONT



BACK

KEY FEATURES

- Quad Input High Definition DVB-T Modulator that converts HD video and audio signals to digital COFDM DVB-T Channel
- Dual Mode - MPEG-2 & AVC (MPEG-4) Encoding
- Distributes 576i / 720P / 1080i / 1080P picture quality (1080P only available on AVC)
- HDMI, Component, CVBS & Analogue Audio Inputs
- Programmable; Channel, Network Names and LCN
- Full function front LCD display for adjustments
- Remote Access and control GUI via Web browser
- Emergency Announcement System control (EAS) input
- Internal FAN Cooling System for Long Life Span
- 2K/8K Carriers
- Adjustable VHF / UHF Output (6-69)
- 20 dB Adjustable Attenuation (98dB launch)
- 1 RU Rack Mountable
- Distributes on any new or existing RF cable
- Most Affordable Price Point for HD distribution
- Installed within minutes – plug n play technology

SPECIFICATIONS

Number of Inputs	4
Video Encoding	MPEG - 2 / AVC (MPEG -4)
Channel Output	6 - 69
Output Connector	F type
Video Input	HDMI / Component / CVBS
Audio Input	HDMI / Analogue Stereo
Video Resolution	576i / 720P / 1080i / 1080P
Output Level	98dBuV
Output Level Adjustment	20 dB typ.

digi-MOD[®] **HD**

